

## Onix Glass - Product Application Chart

Product Name	Wall	Floors	Wet Areas	Pool Floors
Onix - Draco Malla	Yes	No	Yes	No
Nature Blends Upsala White	Yes	Yes	Yes	Yes
Nature Blends Upsala Dark Grey	Yes	Yes	Yes	Yes
Nature Blends Navia	Yes	Yes	Yes	Yes
Onix Mystic Arola	Yes	No	No	No
Onix Mystic Sinai	Yes	No	No	No
Onix Mystic Islande	Yes	Yes	Yes	Yes
Onix Mystic Agata Diamond Brown	Yes	No	No	No
Onix Mystic Savina	Yes	Yes	Yes	Yes
Onix Cosmic Lucca	Yes	No	No	No
Onix Cosmic Livorno	Yes	Yes	No	No
Onix Cosmic Elba	Yes	No	Yes	No
Onix Cosmic Arezzo	Yes	No	Yes	No
Onix Essence Carrara Mix Macauba	Yes	Yes	Yes	Yes
Onix Essence Carrara Mix Grey	Yes	Yes	Yes	Yes

Underlayment should be fully cured concrete or properly installed cement backer-board, and must be dry, stable, flat and free of foreign substances, with no risk of water seepage.

When adhering, apply a thin-layer of adhesive, spreading smoothly in order for it to dry evenly. Back butter each tile to ensure full coverage with adhesive.